



133K X-TRA



Acqua fredda
Cold water



Per uso saltuario
For occasional usage



Lancia getto rotante
Rotary lance

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Carrello a 2 ruote completo di manico
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Sistema di arresto totale dell'idropulitrice a distanza
- Protezione termica del motore
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Motor thermal protector
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:

Pistola
Trigger gun
(4100786)



Testina getto regolabile
Adjustable jet nozzle
(4381820)



Prolunga lancia
Lance extension
(4100775)



Testina getto rotante
Rotary jet nozzle
(4100800)



Tubo AP 6 m
HP hose 6 m
(3083460)



Mini Patio
(3084357)



Portatile
Portable



Battistrada in gomma
Rubber wheels



Porta accessori
Accessories holder



Filtro acqua ispezionabile
Inspectable water filter

Dati Tecnici / Technical Data

MOD	COD	MAX	lt/h						kg
		bar psi	lt/h gph	kw	rpm	Hz	V	kg	
133K X-TRA	14331	140 2000	440 119	1,8	3400	1~50-60	220-240	10,5	

Temperatura massima acqua / Max inlet water temperature
50°C 122°F IPX5-S1

Grandezze logistiche / Logistical Data

EAN code	Dimensione scatola Box dimensions	Q.ty Europallet (800x1200 mm)	Container		Camion Full Truck
			20 ft	40 ft	
	(L x W x H) cm	n°	n°	n°	n°
8016287143318	35x32x58	18	448	924	594

