

164K X-TRA



Acqua fredda
Cold water



Per uso saltuario
For occasional usage



Lancia getto rotante
Rotary lance

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Carrello a 2 ruote completo di manico
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Sistema di arresto totale dell' idropulitrice a distanza
- Protezione termica del motore
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Motor thermal protector
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:

Pistola Trigger gun (4100786)		Testina getto regolabile Adjustable jet nozzle (4101550)	
Prolunga lancia Lance extension (4100775)		Testina getto rotante Rotary jet nozzle (4100800)	
Tubo AP 8 m HP hose 8 m (4102400)		Mini Patio (3085480)	



Elettropompa con pompa con testa in alluminio e motore con protezione termica

Electric motorpump with aluminium head pump and electric motor with thermal protector



Dati Tecnici / Technical Data

MOD	COD	MAX		lit/h		⚡		kg	
		bar	psi	lt/h	gph	kw	rpm	Hz	V
164K X-TRA	15016	165	2393	480	126,8	2,0	50	230~	10,2

Temperatura massima acqua / Max inlet water temperature
50°C 122°F IPX5-S1

Grandezze logistiche / Logistical Data

EAN code	Dimensione scatola Box dimensions (L x W x H) cm	Q.ty Europallet (800x1200 mm)	Container		Camion Full Truck	kg Lordo/Gross
			20 ft	40 ft		
8016287150163	48x32,1x52x5	20	336	672	660	11,1



Filtro acqua ispezionabile
Inspectable water filter